

TRAMIGO

TRACKING & CONNECTIVITY



COMPLETE SOLUTION

PTT-XR

COMPLETE, COMPACT, AND RELIABLE
PUSH-TO-TALK FOR DAILY OPERATIONS



CRYSTAL-CLEAR
SOUND QUALITY



RUGGED AND
USER-FRIENDLY



SECURE
CONVERSATIONS



EASY TEAM
MANAGEMENT



UNLIMITED
TALK RANGE



TRAMIGO PTT-XR

DAILY COMMUNICATION MADE SIMPLE

PTT-XR is a compact and affordable Push-to-Talk over 4G LTE device built for simple, reliable daily communication. Ideal for field professionals in metropolitan environments, it combines real-time communication and built-in tracking in one device. With stable multi-network connectivity, nationwide 4G coverage, and optional global use*, PTT-XR helps teams stay connected and coordinate work more efficiently.

KEY BENEFITS



Loud and clear audio
in busy environments



Instant one-to-one and
group communication



Secure communication



Works over 4G LTE using
smart network selection



Plug-and-play, ready to
use out of the box



Easy to communicate and manage
remote teams from one place



Real-time GPS tracking
and geofencing



eSIM and SIM supported



Lightweight to carry



Energy-efficient design for
longer field operations

**Subject to 4G/LTE network support in the destination country. Additional charges may apply by country. Please contact Tramigo for detailed information on PTT-XR availability in applicable countries.*

+358 50 475 46 06

tramigo.com

sales@tramigo.com

COMMUNICATION WHEREVER THE NETWORK TAKES YOU

Tramigo multi-network connectivity automatically connects your device to the strongest available network. This improves coverage and stability during daily operations.

SINGLE NETWORK

Limited Coverage



MULTI-NETWORK

Wider Coverage



PTT-XR ACCESSORIES & TECHNICAL DATA


STANDARD ACCESSORIES




Battery



Adapter



USB-C cable



Belt Clip

112 mm



32 mm

56 mm

Power	
Working voltage	3.7V
Battery Capacity	3000mAh
Charging Port	USB Type-C
System & Interface	
Language	English
Audio Port	K-type
3GPP Band	LTE-FDD: B1, B3, B5, B7, B8, B20, B28
	LTE-TDD: B38, B40, B41

RF & Performance	
Antenna	Built-in antenna
Receiving sensitivity	-106 dBm
Max transmitting power	23 dBm ± 2 dBm
Physical & Environmental	
Dimension	H: 112mm D: 32mm W: 61mm (top) W: 56mm (bottom)
Weight (with battery)	146g
Working temperature	-20°C ~ +60°C
Storage temperature	-20°C ~ +60°C
Audio output power	2W@10% distortion